

DIRECT READING AIR MONITORING LOG

CLIENT: Los Angeles Unified School District DATE: 12/17/15 PAGE 1 of 2
 LOCATION: Castlebay Lane Elementary School BY: Travis Dagdigian

INSTRUMENT: Ultra RAE 3000 Photo Ionization Detector
 BENZENE FUNCTION TEST: Pass (No Calibration Required) Fail (Conduct Calibration)
 BENZENE SENSOR CALIBRATION VALUE: _____ ppmv CALIBRATION READING: _____ ppmv

INSTRUMENT: Multi RAE
 FUNCTION TEST: Pass (No Calibration Required) Fail (Conduct Calibration)
 CALIBRATION VALUE: H2S _____ ppmv CO _____ ppmv LEL _____ % O2 _____ % IB _____ ppmv
 CALIBRATION READING: H2S _____ ppmv CO _____ ppmv LEL _____ % O2 _____ % IB _____ ppmv


INSTRUMENT: Jerome J631X Hydrogen Sulfide Analyzer
 FUNCTION TEST: Pass (No Calibration Required) Fail (Return to Manufacturer for Calibration)
 CALIBRATION VALUE: N/A Factory Calibrated CALIBRATION READING: Manufacturer Calibration Only

TIME	VOCs (ppmv)	Benzene (ppmv)	% LEL	Hydrogen Sulfide (ppmv)	Drager Tubes				Location
					Benzene (ppmv)	Toluene (ppmv)	Ethylbenzene (ppmv)	Xylene (ppmv)	
0755	0.0	--	0	0.000	--	--	--	--	Main office / Hallways
0815	--	--	--	--	--	--	--	--	Main Office Tedlar collection
0900	0.0	0.0	0	0.000	--	--	--	--	Playground
0930	--	--	--	--	ND	ND	ND	ND	Main Faculty Restroom
1020	0.0	--	0	0.000	--	--	--	--	School Perimeter Parking Lot
1040	--	0.0	--	--	--	--	--	--	Main Office
1120	0.0	--	0	0.000	--	--	--	--	Performing Arts Center
1215	--	--	--	--	ND	ND	ND	ND	Parking Lot
1255	0.0	--	0	0.000	--	--	--	--	Playground
1315	--	0.0	--	--	--	--	--	--	Parking Lot – Back Gate

Weather Conditions: Clear - Calm Wind Speed: 0-2 mph Wind Direction: -- Temperature: 55 °F

Comments: The UltraRAE is used for measuring Volatile Organic Compound (VOC) and Benzene. The MultiRae is used for measuring VOCs and %LEL (used as an indicator of the potential presence of methane). The Jerome J631X is used for measuring Hydrogen Sulfide. Drager tubes are used for measuring Benzene, Toluene, Xylene and Ethylbenzene. %LEL is used as an indicator of methane but is not chemical specific. VOC readings are an indicator of all volatile constituents and are not chemical specific. Real time readings are used to guide sample collection. Samples collected daily are submitted to a laboratory for analyses.

H2S = Hydrogen Sulfide; O2 = Oxygen; % = percent; CO = Carbon Monoxide; LEL = Lower Explosive Limit; IB = Isobutylene ND = Not Detected; ppmv = parts per million by volume; N/A = Not Applicable; -- = No Reading (no measurement taken at this time)



DIRECT READING AIR MONITORING LOG

CLIENT: Los Angeles Unified School District DATE: 12/17/15 PAGE 2 of 2
 LOCATION: Castlebay Lane Elementary School BY: Travis Dagdigian

INSTRUMENT: Ultra RAE 3000 Photo Ionization Detector
 BENZENE FUNCTION TEST: Pass (No Calibration Required) Fail (Conduct Calibration)
 BENZENE SENSOR CALIBRATION VALUE: _____ ppmv CALIBRATION READING: _____ ppmv

INSTRUMENT: Multi RAE
 FUNCTION TEST: Pass (No Calibration Required) Fail (Conduct Calibration)
 CALIBRATION VALUE: H2S _____ ppmv CO _____ ppmv LEL _____ % O2 _____ % IB _____ ppmv
 CALIBRATION READING: H2S _____ ppmv CO _____ ppmv LEL _____ % O2 _____ % IB _____ ppmv

INSTRUMENT: Jerome J631X Hydrogen Sulfide Analyzer
 FUNCTION TEST: Pass (No Calibration Required) Fail (Return to Manufacturer for Calibration)
 CALIBRATION VALUE: N/A Factory Calibrated CALIBRATION READING: Manufacturer Calibration Only

TIME	VOCs (ppmv)	Benzene (ppmv)	% LEL	Hydrogen Sulfide (ppmv)	Drager Tubes				Location
					Benzene (ppmv)	Toluene (ppmv)	Ethylbenzene (ppmv)	Xylene (ppmv)	
1325	0.0	--	0	0.001	--	--	--	--	Main Building Hallways
1327	--	--	--	0.000	--	--	--	--	Main Building Hallways
1330	--	--	--	0.000	--	--	--	--	Main Building Hallways
1405	0.0	--	0	0.000	--	--	--	--	Playground/P. Arts
1430	--	0.00	--	--	--	--	--	--	Playground/P. Arts

Weather Conditions: _____ Wind Speed: _____ Wind Direction: _____ Temperature: _____ °F

Comments: The UltraRAE is used for measuring Volatile Organic Compound (VOC) and Benzene. The MultiRae is used for measuring VOCs and %LEL (used as an indicator of the potential presence of methane). The Jerome J631X is used for measuring Hydrogen Sulfide. Drager tubes are used for measuring Benzene, Toluene, Xylene and Ethylbenzene. %LEL is used as an indicator of methane but is not chemical specific. VOC readings are an indicator of all volatile constituents and are not chemical specific. Real time readings are used to guide sample collection. Samples collected daily are submitted to a laboratory for analyses.

H2S = Hydrogen Sulfide; **O2** = Oxygen; **%** = percent; **CO** = Carbon Monoxide; **LEL** = Lower Explosive Limit; **IB** = Isobutylene **ND** = Not Detected; **ppmv** = parts per million by volume; **N/A** = Not Applicable; **--** = No Reading (no measurement taken at this time)