

LAUSD-OFFICE OF ENVIRONMENTAL HEALTH AND SAFETY

JOB SAFETY ANALYSIS OPERATING A NAIL GUN

General Precautions:


- 1. Operate equipment in strict accordance with Manufacturer's instructions.
- 2. Only authorized users can operate equipment.
- 3. A tool retainer shall be installed in each piece of utilization equipment, which, without such retainer, may eject tool.
- 4. Hose and hose connections used for conducting compressed air to utilization equipment must be designed for the pressure and service to which they are subjected.
- 5. Hearing Protection must be worn when operating pneumatic tools.
- 6. Always wear eye protection.

Required Personal Protective Equipment (PPE)*

Work boots, safety glasses with side shield, hearing protection and safety vest

Required Training

Operation of a nail gun



TASK	HAZARDS	CONTROLS
1. General Use	Trauma, Injury	Do not hold the trigger down unless you are purposefully firing the tool.
		Never point the tool at anyone.
		Never assume the tool is empty.
		Disconnect the air hose before clearing a jam or making adjustments.
		Do not fire the tool unless the nose is firmly pressed against a work piece.
		Keep your free hand out of the way of the tool.
		Wear safety shoes, safety glasses with side shields.
	Fire	Use only compressed air to power the tool, not bottled gas.
		Do not exceed the manufacturer's specified air pressure for the tool, and never exceed 120 psi.
		Do not operate tools around flammables.
	Noise	Use hearing protection.



FS-UTIL-151 Page 1

I have received, read and understood the contents of this JSA and have also acquired the aforementioned required training
NAME:
DEPARTMENT:
JOB TITLE:
EMPLOYEE ID:
DATE:
SIGNATURE:
For more information about this JSA, contact the <i>Office of Environment, Health and Safety</i> at LAUSD, 333 South Beaudry Avenue, 21st Floor, Los Angeles, CA-90017 213-241-3199 • http://achieve.lausd.net/oehs

FS-UTIL-151