



LAUSD-OFFICE OF ENVIRONMENTAL HEALTH AND SAFETY

JOB SAFETY ANALYSIS OPERATING A CHAIN HOIST

- General Precautions:**
1. Operate equipment in strict accordance with Manufacturer's instructions.
 2. Only authorized users can operate equipment.
 3. DO NOT overload hoist beyond its rated capacity.
 4. Report any observed defect or safety hazard to your supervisor immediately.
 5. Inspect the hoist and tie-off point before every use.

Required Personal Protective Equipment (PPE)*

Gloves, work boots, safety vest and hard hat

Required Training

Operation of a chain hoist

*Additional training and PPE may be required depending on the scope of the activities to be performed with piece of equipment, including but not limited to eye and hand protection or electrical safety. All construction work areas must be demarcated and barricaded.



TASK	HAZARDS	CONTROLS
1. General Use	<p>Foot Injury</p> <p>Hand injury</p> <p>Head injury</p> <p>Struck by falling objects</p>	<p>Wear work boots</p> <p>Wear gloves. Beware of pinch points. Maintain situational awareness.</p> <p>Wear a hard hat. Make sure safety latch is in good condition and is engaged. Make sure the tie-off point is stable and adequate for the load. Be careful of the load swinging. All hoists must be inspected and certified annually. Safety training is required before operation, including rigging techniques. Never exceed the maximum load capacity. Do not stand under an elevated load.</p>

I have received, read and understood the contents of this JSA and have also acquired the aforementioned required training.

NAME:	
DEPARTMENT:	
JOB TITLE:	
EMPLOYEE ID:	
DATE:	
SIGNATURE:	

For more information about this JSA, contact the *Office of Environment, Health and Safety* at LAUSD, 333 South Beaudry Avenue, 21st Floor, Los Angeles, CA-90017
213-241-3199 • <http://achieve.lausd.net/oehs>